



INTERNATIONAL® 4300

PRODUCT SPECIFICATIONS

Model Configurations		4300 4x2						Standard	Maximum	
								Front GAW	8,000 lbs	14,000 lbs
								Rear GAW	15,500 lbs	23,000 lbs
								Total GVW	23,500 lbs	37,000 lbs
Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius		
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance	
128	5760	2773	8533	61	100	39	207.0	18ft. 9in.	19ft. 10in.	
140	5827	2757	8584	73	112	39	219.0	20ft. 2in.	21ft. 3in.	
152	5855	2848	8703	85	148	63	255.0	21ft. 7in.	23ft. 9in.	
169	5941	2808	8749	102	165	63	272.0	23ft. 8in.	24ft. 10in.	
175	5971	2794	8765	108	171	63	278.0	24ft. 5in.	25ft. 7in.	
187	6026	2825	8851	120	195	75	302.0	25ft. 10in.	27ft. 0in.	
205	6118	2783	8901	138	213	75	320.0	28ft. 1in.	29ft. 2in.	
217	6193	2868	9011	150	246	96	353.0	29ft. 6in.	30ft. 8in.	
236	6241	2822	9063	169	265	96	372.0	31ft. 10in.	33ft. 0in.	
254	6341	2791	9132	187	283	96	390.0	34ft. 0in.	35ft. 2in.	

		4300 LP 4x2						Standard	Maximum	
								Front GAW	8,000 lbs	8,000 lbs
								Rear GAW	15,500 lbs	19,000 lbs
								Total GVW	23,500 lbs	27,000 lbs
Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius		
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance	
140	5711	2478	8189	73	112	39	219.0	20ft. 1in.	21ft. 3in.	
152	5739	2562	8301	85	148	63	255.0	21ft. 6in.	22ft. 8in.	
169	5824	2521	8345	102	165	63	272.0	23ft. 7in.	24ft. 9in.	
175	5853	2507	8360	108	171	63	278.0	24ft. 4in.	25ft. 6in.	
187	5908	2533	8441	120	195	75	302.0	25ft. 9in.	27ft. 0in.	
205	5998	2490	8488	138	213	75	320.0	27ft. 11in.	29ft. 2in.	
217	6023	2569	8592	150	246	96	353.0	29ft. 5in.	30ft. 7in.	
236	6119	2521	8640	169	265	96	372.0	31ft. 9in.	32ft. 11in.	
254	6218	2489	8707	187	283	96	390.0	33ft. 11in.	35ft. 1in.	

Frame Rails	50,000 PSI 80,000 PSI 120,000 PSI	10.125" 9.125", 10.250" 10.125", 10.250", 10.375"
Front Axle	International	8,000; 10,000; 11,000; 12,000; 14,000 lb Capacity
Front Suspension	Parabolic Taper Leaf w/shocks	8,000; 10,000; 11,000; 12,000; 14,000 lb Capacity
Brakes	Hydraulic Disc, Air	
Steering	Ross, Shepard	
Exhaust System	Frame Mounted Horizontal Muffler Right or Left Side w/ Horizontal or Vertical Tail pipe	
Electrical System	Leece-Neville Delco-Remy America Inc. International Delphi Long Life Halogen Headlights Body Circuit Switches 20 Amps Per Channel, 80 Amps Max Output	110, 140, 160, 200, 270 Amp Alternators 100, 145 Amp Alternators 1100, 1300, 1950 CCA Battery System 1400, 2100 CCA Battery System 6 or 12 Switches in Instrument panel
Front End	Tilting Fiberglass Hood With Three Piece Construction Chrome Grille	
Paint	Base Coat / Clear Coat	
Clutch	Eaton Fuller	
Engine & Equipment	International DT466 Air Cleaner	195 HP/520 lb-ft to 250 HP/660 lb-ft Single/Dual Element w/ optional Integral Snow Valve and In-Cab Control
Transmissions	Fuller Allison	6, 7 Speed Manual 2000, 2400, MD 3060, MD 3560 Series Automatics

Rear Axle	International	12,200; 13,500; 15,500; 17,500; 19,000; 21,000; 22,000; 23,000; 24,000 lb Capacity
Single Rear Suspension	International Air Suspension	12,000; 15,500; 18,500 lb Capacity w/5.3" Ride Height
	International Air Suspension	20,000; 21,00 lb Capacity w/9.25" Ride Height
	Spring Suspension	13,500; 15,500; 18,500; 20,000; 23,500; 31,000 lb Capacity Vari-Rate
Fuel Tank	50 – 140 U.S. Gallons Total Capacity	Right or Left, Right and Left Side Under Cab
Cab	Conventional Steel Cab	107.0" BBC
	6-Man Steel Crew Cab	150.9" BBC
	26" Extended	133.0" BBC
	Conventional Steel Cab	
Interior Trim	Deluxe, Premium	
Mirrors	(02) Rectangular w/Breakaway Type Brackets	
Driver Seats	A wide variety of seats including:	<ul style="list-style-type: none"> • Air-Suspension or Non-Suspension, High Back. • Self-Contained w/ Compressor. • Full Width w/ Fixed Mid Back.
Passenger Seats	A wide variety of seats including:	<ul style="list-style-type: none"> • Two-Man Passenger w/ Storage Compartment • Non-Suspension, High Back • Air-Suspension, High Back
Front Wheels	Steel, Polished Aluminum	19.5", 22.5"; 8, 10 Stud
Rear Wheels	Steel, Polished Aluminum	19.5", 22.5"; 8, 10 Stud
Tires	Goodyear, Michelin	