



# INTERNATIONAL® 4400

## Product Specifications

Model Configurations	4400 4x2	Standard	Maximum
	Front GAW	8,000 lbs	14,000 lbs
	Rear GAW	17,500 lbs	30,000 lbs
	<b>Total GVW</b>	<b>25,500 lbs</b>	<b>44,000 lbs</b>

Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius	
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance
140	5829	3042	8871	73	112	39	219.0	20ft. 9in.	21ft. 10in.
152	5858	3131	8989	85	148	63	255.0	22ft. 3in.	23ft. 4in.
169	5944	3092	9036	102	165	63	272.0	24ft. 5in.	25ft. 6in.
175	5974	3078	9052	108	171	63	278.0	25ft. 2in.	26ft. 3in.
187	6022	3096	9118	120	195	75	302.0	26ft. 8in.	27ft. 9in.
205	6113	3054	9167	138	213	75	320.0	29ft. 11in.	30ft. 0in.
217	6140	3138	9278	150	246	96	353.0	29ft. 1in.	30ft. 2in.
236	6238	3092	9330	169	265	96	372.0	31ft. 4in.	32ft. 6in.
254	6330	3049	9379	187	283	96	390.0	33ft. 6in.	34ft. 8in.

Model Configurations	4400 LP 4x2	Standard	Maximum
	Front GAW	8,000 lbs	8,000 lbs
	Rear GAW	15,500 lbs	19,000 lbs
	<b>Total GVW</b>	<b>23,500 lbs</b>	<b>27,000 lbs</b>

Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius	
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance
140	5750	2777	8527	73	112	39	219.0	20ft. 10in.	21ft. 11in.
152	5780	2859	8639	85	148	63	255.0	22ft. 4in.	23ft. 5in.
169	5869	2816	8685	102	165	63	272.0	24ft. 5in.	25ft. 7in.
175	5898	2803	8701	108	171	63	278.0	25ft. 2in.	26ft. 4in.
187	5946	2816	8762	120	195	75	302.0	26ft. 8in.	27ft. 10in.
205	6035	2774	8809	138	213	75	320.0	29ft. 0in.	30ft. 1in.
217	6064	2852	8916	150	246	96	353.0	29ft. 2in.	30ft. 3in.
236	6155	2807	8962	169	265	96	372.0	31ft. 5in.	32ft. 7in.
254	6245	2764	9009	187	283	96	390.0	33ft. 7in.	34ft. 9in.



# INTERNATIONAL® 4400

## Product Specifications

Model Configurations	4400 6x4	Standard	Maximum
	Front GAW	10,000 lbs	14,000 lbs
	Rear GAW	34,000 lbs	40,000 lbs
	<b>Total GVW</b>	44,000 lbs	54,000 lbs

Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius	
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance
152	6098	5776	11874	85	138	63	255.0	21ft. 8in.	22ft. 9in.
169	6185	5740	11925	102	165	63	272.0	23ft. 9in.	24ft. 10in.
187	6255	5777	12032	120	195	75	302.0	26ft. 0in.	27ft. 1in.
205	6348	5736	12084	138	213	75	320.0	28ft. 2in.	29ft. 3in.
217	6385	5796	12181	150	246	96	353.0	29ft. 8in.	30ft. 9in.
224	6423	5779	12202	157	253	96	360.0	29ft. 7in.	30ft. 8in.
236	6479	5778	12257	169	265	96	372.0	31ft. 0in.	32ft. 1in.
242	6516	5738	12254	175	271	96	378.0	31ft. 8in.	32ft. 9in.
254	6577	5712	12289	187	283	96	390.0	33ft. 1in.	34ft. 3in.

<b>Frame Rails</b>	50,000 PSI	10.125"
	80,000 PSI	9.125", 10.250"
	120,000 PSI	10.125", 10.250", 10.375"

<b>Front Axle</b>	International	10,000; 11,000; 12,000; 14,000 lb Capacity
	Dana Spicer	8,000 lb Capacity

<b>Front Suspension</b>	Parabolic Taper Leaf w/ Shocks	8,000; 10,000; 11,000; 12,000; 14,000 lb Capacity
-------------------------	-----------------------------------	--

<b>Brakes</b>	Hydraulic Disc, Air
---------------	---------------------

<b>Steering</b>	Ross, Sheppard
-----------------	----------------

<b>Exhaust System</b>	Single, Frame Mounted Muffler, Vertical Right Side, Horizontal Right or Left Side w/ Horizontal or Vertical Tail pipe
-----------------------	---



## INTERNATIONAL® 4400

### Product Specifications

<b>Electrical System</b>	Leece-Neville	110, 140, 160, 200, 270, 320 Amp Alternators
	Delco-Remy America Inc.	100, 135, 145 Amp Alternators
	International	1100, 1300, 1950 CCA Battery System
	Delphi	1400, 2100 CCA Battery System
	Long Life Halogen Headlights	
	Body Circuit Switches 20 Amps Per Channel, 80 Amps Max Output	6 or 12 Switches in Instrument panel
<b>Front End</b>	Tilting Fiberglass Hood With Three Piece Construction	
	Chrome Grille	
<b>Paint</b>	Base Coat / Clear Coat	
<b>Clutch</b>	Eaton Fuller	
<b>Engine &amp; Equipment</b>	International DT466 High Torque	225 HP/620 lb-ft to 300 HP/860 lb-ft
	International DT570 Standard Torque	285 HP/800 lb-ft to 330 HP/950 lb-ft
	Air Cleaner	Single/Dual Element w/ optional Integral Snow Valve and In-Cab Control
<b>Transmissions</b>	International	7 Speed Manual
	Fuller	6, 10 Speed Manual
	Eaton Fuller	6 Speed Automated Manual
	Allison	Vocational Series 3000/3500 Automatics
<b>Rear Axle (Single)</b>	International	13,500; 15,500 lb Capacity
	Dana Spicer	17,500; 19,000; 21,000; 22,000; 23,000; 24,000; 26,000; 30,000 lb Capacity
	Spicer	21,000 lb Capacity



## INTERNATIONAL® 4400

### Product Specifications

<b>Rear Suspension (Single)</b>	International Air Suspension	12,000; 15,500; 18,500 lb Capacity w/ 5.3" Ride Height for LP chassis/model 20,000; 21,000 lb Capacity w/ 9.25" Ride Height for STD chassis/model
	Hendrickson Air Suspension	23,000 lb Capacity w/ 9.5" Ride Height
	Steel Spring Suspension	15,500; 18,500; 20,000; 23,500; 31,000 lb Capacity Vari-Rate
<b>Fuel Tank</b>	50 – 140 U.S. Gallons Total Capacity	Mounted Under Cab, Right or Left, Right and Left Side
<b>Cab</b>	Conventional Steel Cab	107.0" BBC
	6-Man Steel Crew Cab	150.9" BBC
	26" Extended	133.0" BBC
	Conventional Steel Cab	
<b>Interior Trim</b>	Deluxe, Premium	
<b>Mirrors</b>	(02) Rectangular w/ Breakaway Type Brackets	
<b>Driver Seats</b>	A wide variety of seats including:	<ul style="list-style-type: none"> <li>• Air-Suspension or Non-Suspension</li> <li>• High or Mid Back</li> <li>• Self Contained w/ Air Compressor</li> <li>• Integral Headrest</li> <li>• Air Lumbar Support</li> </ul>
<b>Passenger Seats</b>	A wide variety of seats including:	<ul style="list-style-type: none"> <li>• Two-Man Passenger w/ Storage Compartment</li> <li>• Air-Suspension or Non-Suspension</li> <li>• High or Mid Back</li> <li>• Integral headrest</li> <li>• SCBA Seats (Pass. &amp; Rear in Crew Cab)</li> </ul>
<b>Front Wheels</b>	Painted Steel, Polished Aluminum	19.5", 22.5"; 8,10 Stud



INTERNATIONAL® 4400

Product Specifications

---

<b>Rear Wheels</b>	Painted Steel, Polished Aluminum	19.5", 22.5"; 8, 10 Stud
<b>Tires</b>	Goodyear, Michelin	